



ANTISEIZE

Anti-Seize Lubricating spray
non-melt. Ops: to 1,100 deg.C.

PROPERTIES:

Temperature Range: -18°C - +1,100°C

Base oil: Semi-synthetic

Water Repellence: Outstanding

Colour: Coppery

Composition:

Micro-fined colloidal graphite, zinc compounds, copper & aluminium in a non-melting, non-volatile, highly adhesive, high heat resistant carrier lubricant.



OPERATIONAL PERFORMANCE

- Does not run, drip or settle out.
- Can be applied to hot surfaces.
- Protects from rust and corrosion from chemical attack.
- Highly water resistant
- Highly resistant to fire - naked flames

AREAS OF APPLICATION:

BiRAL ANTISEIZE prevents threaded fixings seizing at temperatures as high as 1,100°C. whilst also operating under high pressures. A/S's resistance to drying out enhances operations.

Obvious examples of applications are: All threaded fixings in industrial high temp. manufacturing situations. Manifold Bolts, Spark Plugs and wheel bolts etc. Brake Equipment, Clutch Shafts, Valves, Connections and Chains/Conveyors operating at high temperatures, Gaskets etc. Slack bolts will fit better

MODE OF OPERATION

BiRAL Antiseize prevents seizure: Reduces corrosion and the formation of rust. Bolts can be tightened more securely - torque is improved.

A/S is a high pressure resistant lubricant and is extremely resistant to water, naked flames and chemical attack.

A/S effectively prevents metal-to-metal contact and protects against galvanic corrosion.

Facilitates easy stripping down even of hot components.



500ml Cans

DTS Process Technologies Ltd

Meiklewood Business Park-Glasgow Road-Kimarnock-Scotland-KA3 6AG

Tel: +44 (0)1563 534713 - Fax: +44 (0)1563 532543 - www.dtsprocess.com