



SC

Electrical Surface Cleaner

SC: for rapid, efficient cleaning & degreasing of electric motors and equipment.

Equally effective on metals and most plastics

PROPERTIES:

Specific gravity:	1.21
Flash Point: COC:	225°C
MAC (Maximum Acceptable Concentration)	400ppm
MAP (Maximum Aniline Point)	18°C.
Distillation range:	40°C to 170°C.
Moisture Content:	max. 110 ppm
Acidity rating: mg KOH/g:	max. 0.015



OPERATIONAL PERFORMANCE

- BiRAL SC is an efficient, water repellent spray fluid for cleaning electric motors, generators, armatures, brushes, bearings and circuit boards.
- Removes oil, grease and dirt whilst evaporating quickly without leaving oil film,
- Suitable for cleaning metals and virtually all plastics including polyester, polyethylene, polypropylene and PTFE-based materials,
- Will not attack or cause corrosion on metals, - suitable for all phases and types
- BiRAL SC can also be used in conjunction with for ultrasound cleaning processes.
- Excellent for cleaning and dispelling moisture in automobile ignition systems.
- Contains no oils or other lubricants.

User note: Check compatibility with plastics. Do not use on running motors. As with all cleaning fluids take care not to damage insulating seals.



500ml Sprays

DTS Process Technologies Ltd
Meiklewood Business Park-Glasgow Road-Kimarnock-Scotland-KA3 6AG
Tel: +44 (0)1563 534713 - Fax: +44 (0)1563 532543

www.dtsprocess.com